



imagePRESS V1000 shown with optional accessories.

## Product Specifications

### Marking Engine

<b>Technology</b>	Electrophotography	
<b>Print Speed</b>	8.5" x 11":	Up to 101 ipm
	11" x 17":	Up to 52 ipm
	12" x 18":	Up to 50 ipm
	13" x 19":	Up to 48 ipm
	13" x 30":	Up to 28 ipm
<b>Paper Size</b>	Standard:	3.9" x 5.8" to 13" x 19.2"
	Optional:	5.5" x 7.2" to 13" x 51.2"
<b>Paper Capacity<sup>1</sup></b>	Standard:	Up to 1,100 Sheets
	Optional:	Up to 11,100 Sheets
<b>Paper Weight</b>	Standard:	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	Optional:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Envelopes: <sup>2</sup>	No 10, ISO-C5, DL, Monarch, 6" x 9", 9" x 12", 10" x 13"
<b>Automatic Duplexing</b>	Paper Size:	Up to 13" x 51.2" <sup>3</sup>
	Paper Weight:	Up to 150 lb. Cover <sup>4</sup> (400 gsm)
<b>Power Source</b>	(2) Single-Phase 200 -240 V, 50/60 Hz, 20 A	
<b>Weight</b>	904 lb.	
<b>Dimensions</b>	62.3" W x 34.3" D x 40.9" H	

### Input Accessories

<b>Multi-Drawer Paper Deck-E1</b>	<b>Paper Capacity:<sup>1</sup></b>	Up to 5,000 Sheets
	<b>Paper Size:</b>	5.5" x 7.2" to 13" x 19.2"
	<b>Paper Weight</b>	
	Top/Middle:	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	Bottom:	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	<b>Power Source:</b>	110 - 127V, 60 Hz, 7 A
	<b>Weight:</b>	392 lb.
	<b>Dimensions:</b>	38" W x 31.5" D x 42.5" H
<b>POD Deck Lite-C1</b>	<b>Paper Capacity:<sup>1</sup></b>	Up to 3,500 Sheets
	<b>Paper Size:</b>	5.5" x 5.8" to 13" x 19.2"
	<b>Paper Weight:</b>	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	<b>Power Source:</b>	120 - 127 V, 60 Hz, 2.2 A
	<b>Weight:</b>	168 lb.
	<b>Dimensions:</b>	28.2" W x 27" D x 22.6" H
<b>POD Deck Lite XL-A2</b>	<b>Paper Capacity<sup>1</sup></b>	
	Up to 13" x 19.2":	Up to 3,500 Sheets
	Up to 13" x 30":	Up to 1,000 Sheets
	<b>Paper Size:</b>	5.5" x 5.83" to 13" x 30"
	<b>Paper Weight:</b>	
	Up to 13" x 19.2":	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	Up to 13" x 30":	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	<b>Power Source:</b>	120 - 127 V, 60 Hz, 2.2 A
	<b>Weight:</b>	249 lb.
	<b>Dimensions:</b>	43.5" W x 27" D x 22.6" H

Input Accessories (Continued):

<b>Stack Bypass-D1</b>	<b>Paper Capacity:</b> <sup>1</sup>	Up to 250 Sheets
	<b>Paper Size:</b>	3.9" x 5.83" to 13" x 19.2"
	<b>Paper Weight:</b>	14 lb. Bond to 130 lb. Cover (52 gsm to 350 gsm)
	<b>Weight:</b>	3 lb.
	<b>Dimensions:</b>	18" W x 15.1" D x 2.9" H

<b>Long Sheet Feeding and Catch Tray-B1</b>	<b>Paper Capacity:</b>	Up to 1 Sheet
	<b>Paper Size:</b>	8.3" x 19.2" to 13" x 51.2"
	<b>Paper Weight:</b>	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	<b>Weight:</b>	2 lb.
	<b>Dimensions:</b>	24.9" W x 56.1" D x 56.1" H

<b>Duplex Colour Image Reader-P1</b>	<b>Image Sensor:</b>	CCD
	<b>Scan Speed:</b>	Up to 270 opm (Letter, 300 dpi)
	<b>Document Size:</b>	2.8" x 5.5" to 12" x 24.8"
	<b>Resolution:</b>	Up to 600 x 600 dpi, 256 Gradations
	<b>Tray Capacity:</b> <sup>1</sup>	Up to 200 Sheets
	<b>Weight:</b>	51 lb.
<b>Dimensions:</b>	25.7" W x 23.3" D x 8.6" H	

## Finishing Accessories

<b>Sensing Unit-B1<sup>5</sup></b>	<b>Tasks:</b>	Front-to-Back Alignment, Colour Accuracy Check, Cross Shade Adjustment, Secondary Transfer Adjustment
	<b>DFE:</b>	PRISMAsync print server V8.3 or Later; imagePRESS Server D3000 V1.0 or Later
	<b>Paper Weight:</b>	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	<b>Paper Size:</b>	5.5" x 5.83" to 13" x 51.2"
	<b>Power Supply:</b>	100 – 240 V, 50/60 Hz, 2.5 A
	<b>Weight:</b>	222 lb.
	<b>Dimensions:</b>	20.3" W x 29.5" D x 48.3" H

<b>Document Insertion Unit-R1<sup>5</sup></b>	<b>Tray Capacity:</b> <sup>1</sup>	
	Upper Tray:	Up to 200 Sheets
	Lower Tray:	Up to 200 Sheets
	<b>Paper Weight:</b>	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	<b>Paper Size:</b>	7.2" x 7.2" to 13" x 19.2"
	<b>Power Supply:</b>	100 – 240 V, 50/60 Hz, 1.4 A
<b>Weight:</b>	135 lb.	
<b>Dimensions:</b>	29.4" W x 31.2" D x 55.4" H	

<b>Multi Function Professional Puncher-C1<sup>5</sup></b>	<b>Paper Weight</b>	
	Punching:	20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)
	Creasing:	110 lb. Text to 110 lb. Cover (157 gsm to 300 gsm)
	<b>Paper Size</b>	
	Punching:	12" x 18", 11" x 17", Letter, Legal, Letter-R, Statement
	Creasing:	Letter-R, 11" x 17", 12" x 18", 13" x 19"
	<b>Die Set Patterns:</b>	Loose-Leaf 3-Hole/5-Hole, Velo Bind 11-Hole, Plastic Comb 19-Hole, Twin Loop 21-Hole/32-Hole, Colour Coil 44-Hole, Crease
<b>Power Supply:</b>	115 V, 60 Hz, 3.8 A	
<b>Weight:</b>	225 lb.	
<b>Dimensions:</b>	17.5" W x 31.3" D x 40.9" H	

<b>GBC eWire Pro<sup>7</sup></b>	<b>Bound Book Size:</b> <sup>1</sup>	7 to 100 Sheets
	<b>Paper Size:</b>	Letter, 5.5" x 8.5", Tab Stock
	<b>Paper Weight:</b>	20 lb. Bond to 110 lb. Cover (75 gsm to 300 gsm)
	<b>Wire Choices:</b>	1/4", 5/16", 3/8", 7/16", 1/2", 9/16"
	<b>Stack Capacity:</b>	Up to 35 Books
	<b>Power Supply:</b>	115 V, 60 Hz, 2.8A
	<b>Weight:</b>	500 lb.
<b>Dimensions:</b>	35.8" W x 31.3" D x 42.6" H	

<b>Perfect Binder-F1<sup>5</sup></b>	<b>Finished Book Size:</b>	5.4" x 8" to 8.5" x 11.7"
	<b>Book Thickness:</b> <sup>1</sup>	10 to 200 Sheets (Up to 0.98")
	<b>Body Paper Weight:</b>	14 lb. Bond to 43 lb. Bond (52 gsm to 163 gsm)
	<b>Cover Paper Weight:</b>	24 lb. Bond to 110 lb. Cover (90 gsm to 300 gsm)
	<b>Trimming Method:</b>	3-Side Cut/1-Side Cut/No Cut
	<b>Trim Range</b>	
	Top/Bottom:	0.26" to 1.6"
	Side:	0.26" to 1.95"
	<b>Power Source:</b>	208 V, 60 Hz, 3 A
	<b>Weight:</b>	679 lb.
<b>Dimensions:</b>	36.3" W x 31.1" D x 51.2" H	

Finishing Accessories (Continued):

<b>High Capacity Stacker-J1</b>	<b>Stack Capacity:</b> <sup>1</sup>	Up to 6,000 Sheets
	<b>Top Tray Capacity:</b> <sup>1</sup>	Up to 200 Sheets
	<b>Paper Size:</b>	5.5" x 7.2" to 13" x 19.2"
	<b>Paper Weight:</b>	14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm)
	<b>Power Source:</b>	100 – 240 V, 50/60 Hz, 2.5 A
	<b>Weight:</b>	265 lb.
<b>Dimensions:</b>		35.4" W x 29.3" D x 44.9" H

<b>Plockmatic Multi Purpose Stacker<sup>8</sup></b>	<b>Stack Height</b>	Sheets < 25.6": Up to 11.8" Sheets > 25.6": Up to 5.3"
	<b>Paper Size:</b>	8.3" x 11" to 13" x 30"
	<b>Paper Weight:</b>	100 lb. Text to 130 lb. Cover (148 gsm to 350 gsm)
	<b>Power Source:</b>	100 – 240 V, 50/60 Hz, 2 A
	<b>Weight:</b>	168 lb.
	<b>Dimensions:</b>	

<b>Paper Folding Unit-K1<sup>9</sup></b>	<b>Double Parallel Fold:</b>	Legal, Letter-R
	<b>C/Accordion Fold:</b>	Letter-R
	<b>Z-Fold:</b>	Letter-R, 11" x 17"
	<b>Paper Weight:</b>	14 lb. Bond to 28 lb. Bond (52 gsm to 105 gsm)
	<b>Power Source:</b>	From Finisher
	<b>Weight:</b>	157 lb.
<b>Dimensions:</b>		13.2" W x 31.2" D x 46.9" H

<b>Staple Finisher-AF1/ Booklet Finisher-AF1</b>	<b>Tray Capacity</b> <sup>1</sup>	Top Tray: Up to 1,000 Sheets Lower Tray: Up to 4,000 Sheets	
	<b>Paper Weight</b>	Stacking: 14 lb. Bond to 150 lb. Cover (52 gsm to 400 gsm) Corner Stapling: 14 lb. Bond to 120 lb. Cover (52 gsm to 325 gsm) Booklet-Making: 14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)	
	<b>Staple Positions:</b>	Corner, Double-Side	
	<b>Paper Size</b>	Stapling: 7.2" x 8.3" to 11.7" x 17" Saddle Finisher: 8.3" x 11" to 13" x 19.2"	
	<b>Stapling Capacity</b> <sup>1</sup>	Corner/Double Side: <sup>1</sup> Up to 100 Sheets Saddle-Stitch: <sup>1</sup> Up to 25 Sheets V-Fold: Up to 5 Sheets without Stitch	
	<b>Power Source:</b>	120 – 240 V, 50/60 Hz, 8 A	
	<b>Weight</b>	Staple Finisher: 287 lb. Booklet Finisher: 397 lb.	
	<b>Dimensions:</b>		31.5" W x 31.2" D x 48.8" H

<b>Long Sheet Feeding and Catch Tray-D1<sup>9</sup></b>	<b>Stack Capacity:</b> <sup>1</sup>	100 Sheets
	<b>Paper Size:</b>	4" x 5.83" to 13" x 30"

<b>Long Sheet Catch Tray XL-B1<sup>9</sup></b>	<b>Stack Capacity</b> <sup>1</sup>	Up to 30": Up to 300 Sheets Up to 51.2": Up to 10 Sheets
	<b>Paper Size:</b> 4" x 5.83" to 13" x 51.2"	

<b>Puncher Unit-BS1<sup>12</sup></b>	<b>Paper Sizes</b>	2-Hole: Legal, Letter-R, Custom Size (7.2" x 7.2" to 11.7" x 17") 3-Hole: 11" x 17", Letter, Executive-R, Custom Size (9.5" x 7.2" to 11.7" x 17")
	<b>Paper Weight:</b>	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	<b>Punch Waste Capacity:</b>	Up to 6,000 Sheets
	<b>Power Supply:</b> From the Finisher	

<b>DFD Adapter and Finisher Bridge-B1<sup>9</sup></b>	<b>Paper Weight:</b>	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	<b>Supported Finishing:</b>	Plockmatic BLM50/35 SDD BLM300C Plockmatic Multi Purpose Stacker
	<b>Requirements:</b>	Staple/Booklet Finisher-AF1
	<b>Weight:</b>	168 lb.
	<b>Dimensions:</b> 35.8" W x 29.3" D x 46.9" H	

<b>Booklet Trimmer-G1<sup>9</sup></b>	<b>Margin Trimming:</b>	Front-edge Trim
	<b>Trim Amount:</b>	2 mm to 28 mm
	<b>Paper Weight:</b>	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	<b>Power Supply:</b>	From the Finisher
	<b>Weight:</b>	392 lb.
<b>Dimensions:</b>		82.5" W x 31.1" D x 41" H

<b>Two-Knife Trimmer and Conveyor Set<sup>10</sup></b>	<b>Margin Trimming:</b>	Top and Bottom
	<b>Trim Amount:</b>	2 mm to 15 mm
	<b>Paper Weight:</b>	14 lb. Bond to 110 lb. Cover (52 gsm to 300 gsm)
	<b>Power Supply:</b>	120 V, 50/60 Hz, 2.5 A
	<b>Weight:</b>	320 lb.
<b>Dimensions:</b>		21.1" W x 30.3" D x 41" H

<b>SDD Square-Fold Booklet-Maker<sup>10</sup></b>	<b>Booklet Capacity:</b> <sup>1</sup>	Up to 25 Sheets
	<b>Booklet Input Size:</b>	5.5" x 8.27" to 9.6" x 12.6"
	<b>Paper Weight:</b>	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	<b>Power Supply:</b>	120 V, 60 Hz, 15 A
	<b>Weight:</b>	154 lb.
<b>Dimensions:</b>		43.3" W x 23.6" D x 44.9" H

Finishing Accessories (Continued):

<b>SDD Square-Fold Booklet-Maker with Two-Knife Trim<sup>10</sup></b>	<b>Booklet Capacity:<sup>1</sup></b>	Up to 25 Sheets
	<b>Booklet Input Size:</b>	5.5" x 8.27" to 9.6" x 12.6"
	<b>Booklet Output Size:</b>	4.7" x 7.9" to 9.6" x 12.6"
	<b>Paper Weight:</b>	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	<b>Trim Amount:</b>	2 mm to 35 mm
	<b>Power Supply:</b>	120 V, 60 Hz, 15 A
	<b>Weight:</b>	573 lb.
	<b>Dimensions:</b>	62.7" W x 27.6" D x 51.2" H

<b>Plockmatic BLM50/35 Professional Booklet-Maker<sup>8</sup></b>	<b>Booklet Size:<sup>1</sup></b>	Up to 35/50 Sheets
	<b>Paper Size:</b>	8.1" x 10.8" to 12.6" x 18"
	<b>Paper Weight</b>	
	Uncoated:	16 lb. Bond to 110 lb. Cover (60 gsm to 300 gsm)
	Coated:	28 lb. Bond to 110 lb. Cover (105 gsm to 300 gsm)
	<b>Trim Amount</b>	
	Face: <sup>11</sup>	1 mm to 25 mm
	Top/Bottom: <sup>12</sup>	5 mm to 30 mm
	<b>Paper Rotating:<sup>12</sup></b>	8.1" x 10.9" to 9.1" x 12.7"
	<b>Weight:</b>	1,049 lb.
	<b>Dimensions:</b>	114.3" W x 33.8" D x 42.5" H

Print Servers

<b>PRISMAsync Print Server<sup>7</sup></b>	<b>System Software:</b>	Version 8
	<b>CPU:</b>	Intel® Core i7 4770S @ 3.1 GHz
	<b>Memory:</b>	16 GB
	<b>Hard Drive:</b>	1.5 TB
	<b>OS:</b>	Windows® 10
	<b>Standard:</b>	Scheduler, DocBox, G7 Calibration, Page Programmer, Remote Manager, PRISMAlytics Dashboard, Automated Workflows, Multiple Queues, Remote Control
	<b>Optional:</b>	Advanced Imposition, DP Link

<b>imagePRESS Server D3000</b>	<b>Fiery System:</b>	FS500 Pro
	<b>CPU:</b>	Intel® Core i5-6500 3.2GHz up to 3.6GHz with Turbo
	<b>Memory:</b>	8 GB
	<b>Hard Drive:</b>	2 TB
	<b>OS:</b>	Windows® 10
	<b>Standard:</b>	Fiery® Hot Folders, Virtual Printers, Unity Display, Fiery JDF, Fiery Command WorkStation 6, Paper Catalogue, Fiery Spot-On, Fiery Remote Scan, Media Librarian
	<b>Optional:</b>	Graphic Arts Pro Package, Fiery JobMaster, Colour Profiler Suite, Fiery JobFlow, Operator Attention Light, Removable HDD, Integrated Interface, and Stand-NX GL

<sup>1</sup> Based on 20 lb. Bond.

<sup>2</sup> Envelope Attachment Kit required.

<sup>3</sup> POD Deck Lite-XL or Long Sheet Feed and Catch Tray-BI required.

<sup>4</sup> Multi Drawer Paper Deck-EI or POD Deck Lite-CI required.

<sup>5</sup> Staple/Booklet Finisher-AFI or High Capacity Stacker-JI required.

<sup>6</sup> High Capacity Stacker-JI required.

<sup>7</sup> Multi Function Professional Puncher-CI required.

<sup>8</sup> High Capacity Stacker-JI or DFD Adapter and Finisher Bridge-BI required.

<sup>9</sup> Staple/Booklet Finisher-AFI required.

<sup>10</sup> Booklet Trimmer-KI required.

<sup>11</sup> Optional trimmer required.

<sup>12</sup> Optional rotator required.

As an ENERGY STAR® Partner, Canon U.S.A., Inc. qualified this model as meeting the ENERGY STAR® energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered Canadian marks. Canon and imagePRESS are registered trademarks of Canon Inc. in Canada and may also be registered trademarks or trademarks in other countries. PRISMA is a registered trademark of Canon Production Printing Netherlands B.V. All other referenced product names and marks are trademarks of their respective owners. Some printer output images may be simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims on unauthorized copying.

©2022 Canon Canada Inc. All rights reserved.



www.canon.ca

