



[DOWNLOAD SPECS](#)

Color imageRUNNER C3326i

Main Unit

Type

A3 Colour Laser Multifunctional

Core Functions

Standard: Print, Copy, Scan, Send
Optional: Fax

Processor

1.6 GHz Dual Core Processor

Control Panel

7" TFT LCD WSVGA Colour Touch-panel

Memory

2.0 GB RAM

Storage

Standard: (eMMC) 64GB
Optional: (SSD) 256GB

Interface Connection

Network

Standard: 1000Base-T/100Base-TX/10Base-T/ Wireless LAN (IEEE802.11b/g/n)

Others

Standard: USB 2.0 (Host) x 2, USB 2.0 (Device) x 1

Paper Capacity (LTR, 20 lb. Bond)

Standard: 1,200 Sheets

Maximum: 2,300 Sheets (with optional Cassette Feeding Unit-AW1)

Paper Sources (LTR, 20 lb. Bond)

Standard: Dual 550-sheet Paper Cassettes, 100-sheet Multipurpose Tray

Optional: Dual 550-sheet Paper Cassettes (Cassette Feeding Unit-AW1)

Paper Output Capacity (LTR, 20 lb. Bond)

Standard: 250 Sheets

Maximum: 650 Sheets (with optional Inner Finisher-L1 and Copy Tray-T1)

Finishing Capabilities

Collate, Group, Offset, Staple, Hole Punch, Eco Staple, Staple On Demand

** Finishing capabilities vary, depending on the options selected*

Supported Media Types

Multi-purpose Tray: Thin, Plain, Heavy*, Recycled, Coated, Colour, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Envelope

* SRA3 is unsupported for Coated (257-300gsm) and Heavy (257-300gsm) paper

Upper Cassette: Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency, Pre-punched, Letterhead, Envelope*

* Envelope Feeder Attachment Kit B (standard) is required.

Lower Cassette: Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency, Pre-punched, Letterhead, Envelope*

* Envelope Attachment Kit A (standard) is required.

Supported Media Sizes

Multi-purpose tray: Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom size: 98.4 x 139.7 mm to 320.0 x 457.2 mm

Envelopes: COM10 No.10, Monarch, ISO-C5, DL Envelope custom size: 98.0 x 98.0 mm to 320.0 x 457.2 mm

Upper Cassette: Standard size: A4, A5, A5R, A6R, B5 Custom size: 105.0 x 148.0 mm to 297.0 x 215.9 mm

Envelope: ISO-C5

* Envelope Feeder Attachment Kit B (standard) is required.

Lower Cassette:

Standard size: A3, A4, A4R, A5, A5R, A6R, B4,
B5, B5R Custom size: 105.0 x 148.0 mm to 304.8 x 457.2 mm

Envelope*: COM10 No.10, Monarch, DL

* Envelope Attachment Kit A (standard) is required.

Supported Media Weights

Multi-purpose tray: 52 to 300 gsm
Upper/Lower Cassette: 52 to 256 gsm
Duplex: 52 to 220 gsm

Print/Copy Speed (BW and Colour)

Letter: Up to 26 ppm
Letter-R: Up to 20 ppm
Legal: Up to 15 ppm
11" x 17": Up to 15 ppm

Warm-up Time

From Power On: Approx. 10 Seconds (Time from device power-on, until copy ready - not print reservation)
From Sleep Mode: Approx. 10 Seconds (Time from exiting Sleep mode to when printing is operational)
Quick Startup Mode: Approx. 4 Seconds (Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display)

Dimensions (W x D x H)

565 x 687 x 891 mm

Installation Space (W x D)

1168 x 1116 mm

Weight

Approx. 74.7 kg including toner

Print Specifications

Print Resolution (dpi)

Up to 1200 x 1200

Standard Page Description Languages

Standard: UFR II, PCL6
Optional: Adobe® PostScript®3TM

Supported File Types

Supported file types:
RUI: PDF, EPS, TIFF/JPEG, XPS

USB Memory: PDF, TIFF/JPEG, XPS
Network Place: PDF, TIFF/JPEG, XPS

Printing from Mobile Devices and Cloud-based Services

AirPrint, Mopria® Print Service, Canon PRINT Business, uniFLOW Online and Universal Print by Microsoft
A range of software solutions is available to provide printing from mobile devices and cloud-based services depending on your requirements. Please contact your sales representative for further information

Fonts

*PS fonts: 136 Roman
PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andale Mono WT J/K/S/T*1 (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts*2*

**1 Requires optional PCL INTERNATIONAL FONT SET-A1
2 Requires optional BARCODE PRT KIT-D1

Operating System

*UFR II: Windows® 8.1/10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022,
Mac OS X (10.11 or later)*

PCL: Windows®8.1/10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022

*PS: Windows®8.1/10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022,
Mac OS X (10.11 or later)*

PPD: Windows® 8.1/10/11, Mac OS X (10.11 or later)

OS Standard Printing

Android/Windows® 10/Windows® 11/Chrome OS/macOS (11.2.2 or later), iOS (15.2 or later), iPadOS

Print Features

Secure Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing, Mixed Paper Sizes/ Orientations, Toner Reduction, Poster Printing, Forced hold printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer

Copy Specifications

First-Copy-Out-Time (LTR)	(BW/CL): Approx. 7.0 / 8.7 seconds or less
Copy Resolution (dpi)	600 x 600
Multiple Copies	Up to 999
Copy Density	Automatic or Manual (9 Levels)
Magnification	25%-400% (1% Increments)
Preset Reduction/Enlargement	25%, 50%, 70%, 100%, 141%, 200%, 400%
Copy Features	Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Book to Two Pages, Two-sided Original, Sort, Job Build, N on 1, Different Size Originals, Sharpness, Erase Frame, Copy ID Card, Skip Blank Pages, Free Size Original, Colour Mode, Reserved copy, Copy Sample

Scan Specifications

Type	Standard: Duplexing Automatic Document Feeder [2-sided to 2-sided]
Document Feeder Paper Capacity	Up to 100 Sheets
Document Feeder Supported Media Sizes	11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Custom Size: 2-3/4" to 12" x 17"
Document Feeder Supported Media Weights	1-sided scanning: 30 to 128 gsm (BW), 64 to 128 gsm (CL) 2-sided scanning: 50 to 128 gsm (BW), 64 to 128 gsm (CL)

Platen Acceptable Originals	Sheet, Book, 3-Dimensional Objects
Platen Maximum Scanning Size	Up to 11-3/4" x 17"
Pull Scan	Colour Network ScanGear2. For both TWAIN and WIA Supported OS: Windows® 8.1/10/11/ Server2012/Server2012 R2/Server 2016/Server 2019/Server2022
Scan Resolution (dpi)	Scan for Copy: up to 600 x 600 Scan for Send: (Push,BW) up to 600 x 600, (Pull,BW) up to 600 x 600 (Push,CL) up to 300 x 300, (Pull,CL) up to 300 x 300 Scan for Fax: up to 600 x 600
Scan to Mobile Devices and Cloud-based Services	A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.
Scan Speed	DADF (ipm: BW/CL, A4): 1-sided Scanning: 70/70 (300 dpi, send), 51/42 (600 dpi, copy) 2-sided Scanning: 35/35 (300 dpi, send), 25.5/25.5 (600 dpi, copy)
Scan Method	PushScan, PullScan, Scan to Network, Scan to USB Memory Key, Scan to Mobile device, Scan to cloud-based services (uniFLOW Online/Online Express)

Send Specifications

Destination	<i>Standard: E-mail/Internet FAX (SMTP), SMB3.1.1, FTP, WebDAV, Optional: Super G3 FAX</i>
Address Book	LDAP (2,000)/Local (1,600)/Speed Dial (200)
Send Resolution (dpi)	<i>Push: 100 x 100, 150 x 150, 200 x 100 (Normal), 200 x 200 (Fine), 200 x 400*(SuperFine), 300 x 300, 400 x400*(UltraFine), 600 x 600*</i>

Pull: 75 x 75, 100 x 100, 150 x 150, 200 x 200,
300 x 300, 400 x 400*, 600 x 600*

*Colour mode is black and white only

Communication Protocol

File: FTP (TCP/IP), SMB3.1.1 (TCP/IP), WebDAV

Email/iFax: SMTP (send), POP3 (receive)

File Format

Standard: TIFF (MMR), JPEG *, PDF (Compact, Searchable, PDF/A-1b, Encrypted), XPS (Compact, Searchable), PDF/XPS (Device Signature, Office Open XML (PowerPoint, Word))
Optional: PDF (Trace & Smooth), PDF/XPS (User Signature)
*Single page only

Universal Send Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation

Fax Specifications

Maximum Number of Connection Lines

1

Modem Speed

Super G3: 33.6 kbps

G3: 14.4 kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

Sending/Recording Size

Statement-R to 11" x 17"

Fax Memory

Up to 30,000 Pages

Speed Dials

Max. 200

Group Dials/Destinations	Max. 199 Dials
Sequential Broadcast	Max. 256 Addresses
Memory Backup	Yes
Fax Features	Sender's Name (TTI), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Interrupt Transmission, Sequential Broadcasting, Password/Subaddress Sending, Confidential Mailbox

Store Specifications

Memory Media	Standard: USB Memory
---------------------	----------------------

Security Specifications

Authentication and Access Control	<p><i>User Authentication (Picture Login, Picture and PIN Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)</i></p>
Document Security	<p><i>Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print*1), Recieve Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/ XPS*2), Send Data Security (Restricted E-mail/ File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/ Restrict Sending from History, S/MIME Support)</i></p> <p style="text-align: center;"><i>*1 Requires optional uniFLOW Online / uniFLOW</i></p> <p style="text-align: center;"><i>*2 Requires optional Universal Send Digital User Signature Kit-C1</i></p>
Network Security	<p><i>8TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0, WPA3 support, Firewall Functionality (IP/ MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired</i></p>

LAN), Disabling/Enabling (Network Protocols/ Applications, Remote UI, USB Interface), G3
FAX separation from LAN, USB Port separation from LAN, Scan and Send -Virus Concerns for
E-mail
Reception

Device Security Standard Storage Initialize, Job Log Conceal Function, Protecting MFP Software Integrity,
Checking MFD Software Integrity & Platform
Firmware Resiliency (NIST SP800-193) with Automatic System Recovery (Verify System at
Startup, Runtime Intrusion Detection enabled with McAfee Embedded Control),

**Device Management
and Auditing** Administrator Password, Digital Certificate and Key Management, Audit Log, Cooperating
with External Security Audit System (Security
Information and Event Management), Security Policy Setting, Remote Management Two-
factor Authentication

Environmental Specifications

Operating Environment

Temperature: 10 to 30°C
Humidity: 20 to 80% RH (Relative Humidity)

Power Requirements

220-240V 50/60Hz 4A

Power Consumption

Maximum: Approx. 1,500 W
Standby: Approx. 44 W*1
Sleep mode: Approx. 2.0W*2, Approx. 1.0W*3
*1 Reference value: measured one unit
* Wireless LAN power serve mode OFF
* Wireless LAN power serve mode ON
**3 Sleep mode is not available in all circumstances due to
certain settings.

Typical Electricity Consumption (TEC)*: 0.32 kWh

*Note: As per US Energy Star 3.0

Noise Levels

Sound Power Level (LWA,m) Active (1-sided) : 6.0B*1, 0.3B*1
Sound Pressure Level (LpAm) Bystander's position: Active (1-sided) : 46 dB*1
*1 Reference value: measured only one unit with ISO7779, described with ISO9296:2017

Consumables

Toner GPR-66 Toner [GPR-66L also available for Colour (C, M, Y). Yield (estimated @ 5% coverage) is 11,000 images.]
