



[DOWNLOAD SPECS](#)

Color imageRUNNER ADVANCE DX C3926i

Main Unit

Type	Colour Laser Multifunctional
Core Functions	<i>Standard:</i> Print, Copy, Scan, Send, Store <i>Optional:</i> Fax
Processor	1.8 GHz Dual Core Processor
Control Panel	10.1" TFT LCD WSVGA Colour Touch-panel
Memory	3.5 GB RAM
Solid State Drive	Standard: 256 GB Maximum: 1 TB
Interface Connection	Network <i>Standard:</i> 1000Base-T/100Base-TX/10Base-T <i>Optional:</i> Wireless LAN Board F-1

Others

Standard: USB 2.0 x1 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device)

Optional: Copy Control Interface, Serial Interface

**Paper Capacity (LTR,
20 lb. Bond)**

Standard: 1,200 Sheets
Maximum: 2,300 Sheets

**Paper Sources (LTR,
20 lb. Bond)**

Standard: Dual 550-sheet Paper Cassettes, 100-sheet Multipurpose Tray
Optional: Dual 550-sheet Paper Cassettes (Cassette Feeding Unit-AW1)

**Paper Output
Capacity (LTR, 20 lb.
Bond)**

Standard: 250 Sheets
Maximum: 3,450 Sheets (with Staple Finisher-AE1/Booklet Finisher-AE1 and Copy-Tray-T1)

Finishing Capabilities

Standard: Collate, Group
With Finishers: Collate, Group, Offset, Staple, Saddle Stitch, Hole Punch, Eco Staple, Staple on Demand

**Supported Media
Types**

Multi-purpose Tray: Thin, Plain, Heavy, Recycled, Coated, Colour, Tracing, Bond, Transparency, Label, Pre-punched, Envelope, Postcard, Letterhead
Upper Cassette: Thin, Plain, Heavy, Recycled, Colour, Tracing, Bond, Transparency, Pre-punched, Envelope, Postcard, Letterhead
Lower Cassette: Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency, Pre-punched, Envelope (Included Envelope Feeder Attachment is required), Letterhead, Postcard

**Supported Media
Sizes**

Multi-Purpose Tray: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Custom Size/Free Size: : 4" x 5-7/8" to 12" x 18", Envelopes (COM10 No. 10, Monarch, ISO-C5, DL), Envelope Custom Size (3-7/8" x 3-7/8" to 12-5/8" x 18")
Upper Cassette: Letter, Executive, Statement-R, Custom Size (4-1/8" x 5-7/8" to 11-3/4" x 8-1/2"), Envelopes (ISO-C5)
Lower Cassette: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R, Custom Size (4-1/8" x 5-7/8" to 12" x 18"), Envelopes (COM10 No. 10, Monarch, DL)

**Supported Media
Weights**

Cassettes: 14 lb. Bond to 140 lb. Cover (52 to 256 g/m²)
Multi-purpose Tray: 14 lb. Bond to 110 lb. Cover (52 to 300 g/m²)
Duplexing: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m²)

**Print/Copy Speed
(BW and Colour)**

Letter: Up to 26 ppm
Letter-R: Up to 20 ppm
Legal: Up to 15 ppm
11" x 17": Up to 15 ppm

Warm-up Time	<p><i>From Power On:</i> Approx. 10 Seconds (Time from device power-on, until copy ready - not print reservation)</p> <p><i>From Sleep Mode:</i> Approx. 10 Seconds (Time from exiting Sleep mode to when printing is operational)</p> <p><i>Quick Startup Mode:</i> Approx. 4 Seconds (Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display)</p>
Dimensions (W x D x H)	22-1/4" x 28-1/2" x 35-3/8" (565 mm x 722 mm x 897 mm)
Installation Space (W x D)	<p><i>Basic:</i> Multi-purpose Tray + Cassette Drawers open: 38-1/2" x 44-1/8" (With right cover open + Multi-purpose tray extension extended + paper cassette open)</p> <p><i>Fully Configured:</i> 65" x 44-1/8" (Includes Staple Finisher-AE1/Booklet Finisher-AE1 + Copy Tray-T1 extension extended + paper cassette open)</p>
Weight	Approx. 187.4 lb. (includes toner)

Print Specifications

Print Resolution (dpi)	1200 x 1200, 1200 x 600
Standard Page Description Languages	UFR II, PCL [®] 6, Adobe [®] PS [®] 3
Supported File Types	PDF, TIFF, JPEG, EPS, XPS
Printing from Mobile Devices and Cloud-based Services	A range of standard and optional software and MEAP-based solutions (including AirPrint, Mopria [®] Print Service, Google Cloud Print, Canon PRINT Business, and uniFLOW Online) are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.
Fonts	<p><i>PCL Fonts:</i> 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese, Korean, Simplified and Traditional Chinese - requires the optional PCL International Font Set-A1), Barcode Fonts (requires the optional Barcode Printer Kit-D1)</p> <p><i>PS Fonts:</i> 136 Roman</p>
Operating System	<p><i>UFR II/PS:</i> Windows[®] Windows[®] 10/11/Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2022, macOS (10.13 or later)</p> <p><i>PCL:</i> Windows[®] 10/11/Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2022</p>

PS: Windows® 10/11/Server 2012/Server 2012 R2/Server 2016/Server 2019/Server 2022, macOS (10.13 or later)

PPD: Windows® Windows® 10/11, macOS (10.13 or later)

Note: Other operating systems and environments including AS/400/UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

Copy Specifications

First-Copy-Out-Time (LTR)	As fast as 6.1 seconds (BW)/8.4 seconds (Colour)
----------------------------------	--

Copy Resolution (dpi)	600 x 600
------------------------------	-----------

Multiple Copies	Up to 999
------------------------	-----------

Magnification	25%-400% (1% Increments)
----------------------	--------------------------

Preset Reduction/Enlargement	25%, 50%, 64%, 73%, 78%, 100% (1:1), 121%, 129%, 200%, 400%
-------------------------------------	---

Scan Specifications

Type	Single-pass Duplexing Automatic Document Feeder
-------------	---

Document Feeder Paper Capacity	Up to 200 Sheets (20 lb. Bond)
---------------------------------------	--------------------------------

Document Feeder Supported Media Sizes	11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Custom Size: 2-3/4" to 12" x 17"
--	--

Document Feeder Supported Media Weights	BW/Colour Original: 13.3 lb. Bond to 80 lb. Cover (50 to 220 g/m ²)
--	---

Platen Acceptable Originals	Sheet, Book, 3-Dimensional Objects
------------------------------------	------------------------------------

Platen Maximum Scanning Size	Up to 11-3/4" x 17"
-------------------------------------	---------------------

Pull Scan	Colour Network ScanGear2 for both Twain and WIA
------------------	---

Scan Resolution (dpi)

Scan for Copy: 600 x 600
Scan for Send: Push (600 x 600), SMB/FTP/WebDAV, Pull (600 x 600)
Scan for Fax: 600 x 600

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to mobile devices and cloud-based services depending on your requirements.

Scan Speed (LTR)

Single Sided Scanning: BW: 135 ipm (300 dpi), CL: 80 ipm (600 dpi)
Double Sided Scanning: BW: 270 ipm (300 dpi), CL: 160 ipm (600 dpi)

Send Specifications

Destination

Standard: E-mail/Internet FAX (SMTP), SMB 3.0, FTP, WebDAV, Mail Box
Optional: Super 3 FAX, IP Fax

Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

Send Resolution (dpi)

Push: Up to 600 x 600 dpi
Pull: Up to 600 x 600 dpi

Communication Protocol

File: FTP (TCP/IP), SMB 3.0 (TCP/IP), WebDAV
Email: SMTP, POP3

File Format

TIFF, JPEG, PDF(Compact, Searchable, Apply Policy, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)

Fax Specifications

Maximum Number of Connection Lines

2

Modem Speed

Super G3: 33.6 Kbps
G3: 14.4 Kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)	400 x 400, 200 x 400, 200 x 200, 200 x 100
Sending/Recording Size	Statement-R to 11" x 17"
Fax Memory	Up to 30,000 Pages (2,000 Jobs)
Speed Dials	Max. 200
Group Dials/Destinations	Max. 199 Dials
Sequential Broadcast	Max. 256 Addresses
Memory Backup	Yes

Store Specifications

Mail Box Simple (Number Supported)	100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, Maximum 10,000 Pages (2,000 Jobs Stored)
Advanced Box	<p><i>Communication Protocol: SMB or WebDAV Supported</i></p> <p><i>Client PC: Windows (Windows 10/11)</i></p> <p>Concurrent Connections (Max.)</p> <p><i>SMB: 64</i></p> <p><i>WebDAV: 3 (Active Sessions)</i></p>
Advanced Box Available Disc Space	Approx. 16 GB (Standard SSD) (With Optional: max. 480 GB)

Security Specifications

Authentication and Access Control	<p><i>User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express17 (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)</i></p> <p><i>Optional: uniFLOW, uniFLOW Online</i></p>
--	--

Document Security

Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle® Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Space Access Control), Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark)

Network Security

TLS 1.3, IPSec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), Communication Line Separation (G3 FAX, USB Port, Advanced Space, Scan and Send-Virus Concerns for E-mail Reception)

Device Security

Protecting SSD Data [SSD Data Encryption (FIPS140-2 Validated), SSD Lock], Standard SSD Initialize, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFP Software Integrity, Automatic Recovery, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection)

Device Management and Auditing

Administrator Password, Digital Certificate and Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting

Environmental Specifications

Operating Environment

*Temperature: 10 to 30°C
Humidity: 20 to 80% RH (Relative Humidity)*

Power Requirements

110V-127V, 60Hz, 8.5A

Power Consumption

*Maximum: Approx. 1,500 W
Sleep Mode: Approx. 0.8 W (not available in all circumstances due to certain settings)
Typical Electricity Consumption (TEC) Rating: 0.30 kWh (based on ENERGY STAR® Product Specification for Imaging Equipment Version 3.0)*

Standards

ENERGY STAR® Certified

Consumables

Toner GPR-66 Toner [GPR-66L also available for Colour (C, M, Y). Yield (estimated @ 5% coverage) is 11,000 images.]
