



[DOWNLOAD SPECS](#)

imagePROGRAF GP-2000

Main Unit Specs

Printer Type	10-colour pigment ink plus Fluorescent Pink Ink
Number of Nozzles	Total: 18,432 All colours: 1,536 nozzles
Nozzle Pitch	600 dpi x 2 Non-firing nozzle detection and compensation
Print Resolution (Up to)	2400x1200dpi (Max)
OS Compatibility	32bit: Windows® (Vista/7/8, 8.1/10) 64bit: Windows 7, Windows 8.1, Windows 10 Windows Server 2008R2 , Windows Server 2012/2012R2 Windows Server 2016 , Windows Server 2019 Mac (OS X 10.10.5 ~ OS10.11), (OS 10.12 ~ macOS 10.14)
Standard Interfaces	USB 2.0 High-Speed 10/100/1000 Base-T/TX Wireless LAN (IEEE 802.11 b/g/n) USB Thumb Drive
Media Thickness	Roll: 0.07 - 0.8 mm (2.8 - 31.5mil)
Ink Droplet Size	Minimum 4 picoliter
Maximum Roll Print Length	Roll Feed - 59' (18 meters)**
Ink Capacity	160ml, 330ml, or 700ml per colour
Maximum Media Roll Diameter	6.7" (170mm)
Ink Type	10 Pigment colour based plus Fluorescent Pink Ink
Borderless Printing	All Sizes
Width Set	Photo Black, Matte Black, Cyan, Magenta, Yellow, Green, Gray, Red, Orange, Violet + Fluorescent Pink
Paper Feed Method	Roll Feed: One Roll, Front-loading, Front Output
Hard Drive	500 GB Manual Feed: Front-loading, Front Output
Media Width Languages	Cut Sheet - 6" - 24" Swift Graphic Raster (SGRaster) Roll Feed - 6" - 24"

	USB Thumb Drive
Media Thickness	Roll: 0.07 - 0.8 mm (2.8 - 31.5mil)
Ink Droplet Size	Minimum 4 picoliter
Maximum Roll Print Length	Roll Feed - 59' (18 meters)**
Ink Capacity	160ml, 330ml, or 700ml per colour
Maximum Media Roll Diameter	6.7" (170mm)
Ink Type	10 Pigment colour based plus Fluorescent Pink Ink
Borderless Printing Width Color Set	All Sizes Photo Black, Matte Black, Cyan, Magenta, Yellow, Green, Gray, Red, Orange, Violet + Fluorescent Pink
Paper Feed Method Hard Drive	Roll Feed: One Roll, Front-loading, Front Output 500 GB Manual Feed: Front-loading, Front Output
Media Width Languages	Cut Sheet - 6" - 24" Swift Graphic Raster (SGRaster) Roll Feed - 6" - 24"
Noise Level Approx	Operation: 48 dB (A) or less Acoustic Power: 6.5 Bels or less
Physical Dimensions	46" (H) x 44" (W) x 39" (D)
Weight	approx.225 lbs (roll holder included, no inks, no print heads)
Power Source	AC 100-240V (50-60Hz)
Power Consumption	Maximum: 84 W or less Standby 2.0 W or less Power Off: 0.3 W or less
Operating Environment	Temperature: 59 - 86°F Relative Humidity: 10-80% (No Condensation)
User-replaceable items	Print Head (PF-10) Maintenance Cartridge (MC-30) Ink Tanks (PFI-2100/PFI-2300/PFI-2700)
Software Included	Professional Print & Layout, Quick Utility Toolbox, Accounting Manager, Device Management Console, Media Configuration Tool, PosterArtist Lite (PC only), PosterArtist (Available for purchase, PC only), Printer Driver Extra Kit (Free Layout and Advanced Preview), Direct Print Plus (PC only), Free Layout Plus (PC only)