



[DOWNLOAD SPECS](#)

## imagePROGRAF GP-6600S

### Specifications

<b>Print Head</b>	PF-10
<b>Number of Nozzles</b>	Number of Nozzles 18,432 nozzles
<b>Droplet Size</b>	Minimum 4 pL per colour
<b>Ink Type</b>	MBK, BK, C, M, Y, GY, O
<b>Ink Tank</b>	Shipped with: 330ml Tank, Each Colour MBK/BK/C/M/Y/GY/O  Replacement: <ul style="list-style-type: none"> <li>• 160 ml PFI-3100 (BK, C, M, Y, GY)</li> <li>• 160 ml PFI-2100 (MBK, O)</li> <li>• 330 ml PFI-3300 (BK, C, M, Y, GY)</li> <li>• 330 ml PFI-2300 (MBK, O)</li> <li>• 700 ml PFI-3700 (BK, C, M, Y, GY)</li> <li>• 700 ml PFI-2700 (MBK, O)</li> </ul>
<b>Printer RAM</b>	Standard Memory: 3 GB Hard Disk: 500 GB
<b>Media Feed</b>	Front-Loading Roll Feed: Two Rolls*, Front Output *If multifunction roll is used
<b>Media Width</b>	Roll Feed: 6" - 60" (152.4 - 1,524 mm) Cut Sheet: 6" - 60" (152.4 - 1,524 mm)
<b>Media Cutter</b>	Automatic horizontal cutting (Rotary cutter): standard
<b>Media Thickness</b>	0.002" - 0.03" (0.07 mm - 0.8 mm)

<b>Media Core Sizes</b>	2" Core Standard, 2"/3" Core Roll Holder Set GP-4600S (RH2-46) and GP-6600S (RH2-66)
<b>Maximum Roll Outer Diameter</b>	6.7" or less (170 mm or less)
<b>Media Output</b>	Catch Basket
<b>Printing Software Utilities</b>	Accounting Manager, Device Management Console, Direct Print Plus, Free Layout Plus, imagePROGRAF Printer Driver for Windows®/Mac®, Media Configuration Tool, PosterArtist, Canon Print Service, Professional Print & Layout
<b>Operating System</b>	Windows 7 (32/64-bit), Windows 8.1 (32/64-bit), Windows 10 (32/64-bit), Windows 11 (64-bit), Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 (64-bit) Macintosh OS v10.12.6 - v13x
<b>Print Language</b>	SGRaster (Swift Graphic Raster), PDF, JPEG
<b>Interface</b>	Standard (Built-in): USB 2.0 Hi-Speed, 10/100/1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g/n)* *Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.
<b>Power Supply</b>	AC 100 – 240V (50 – 60 Hz)
<b>Power Consumption</b>	Max: Approx. 94W Standby: Approx. 1.7W Power Off: Approx. 0.1W
<b>Certifications</b>	ENERGY STAR® (Worldwide), EPEAT Gold
<b>Operational Environment</b>	Temperature: 59 – 86 °F (15 – 30 °C) Relative Humidity: 10 – 80% (Non Condensation)
<b>Printer Dimensions (W x D x H) and Weight</b>	With stand and basket open: 78.7" x 38.7" x 46", 373 lbst Main unit with pallet: 87.7" x 36" x 41=0.4", 481 lbs Multifunction Roll Unit (physically strapped to printer): 84.0" x 22.1" x 18.1", 92.6 lbs
<b>Options</b>	<ul style="list-style-type: none"> <li>• 2"/3" Roll Holder Set GP-4600S (RH2-46) &amp; GP-6600S (RH2-66)</li> </ul>
<b>User Replaceable Items</b>	<ul style="list-style-type: none"> <li>• Ink Tank: PFI-3100/PFI-2100 (160ml), PFI-3300/PFI-2300 (330ml), PFI-3700/PFI-2700 (700ml)</li> <li>• Print Head (PF-10)</li> <li>• Maintenance Cartridge (MC-30)</li> <li>• Cutter Blade (CT-07)</li> </ul>