



[DOWNLOAD SPECS](#)

## imagePROGRAF PRO-6600

### Specifications

<b>Print Head</b>	PF-10
<b>Number of Nozzles</b>	18,432 nozzles
<b>Droplet Size</b>	4 pL per Colour
<b>Ink Type</b>	Pigment: BK, MBK, C, M, Y, PC, PM, GY, PGY, R, B, +CO
<b>Ink Tank</b>	<p>Shipped with: 330 ml of each colour MBK, BK, C, M, Y, GY, PGY, PC, PM, R, B, CO</p> <p>Replacement:</p> <ul style="list-style-type: none"> <li>• 160 ml PFI-3100 (BK, C, M, Y, GY, PGY, PC, PM, R, B, CO), 160 ml PFI-2100 (MBK)</li> <li>• 330 ml PFI-3300 (BK, C, M, Y, GY, PGY, PC, PM, R, B, CO), 330 ml PFI-2300 (MBK)</li> <li>• 700 ml PFI-3700 (BK, C, M, Y, GY, PGY, PC, PM, R, B, CO), 700 ml PFI-2700 (MBK)</li> </ul>
<b>Printer RAM</b>	<p>Standard Memory: 3 GB</p> <p>Hard Disk: 500 GB</p>
<b>Media Feed</b>	<p>Front-Loading Roll Feed: Two* Rolls, Front Output</p> <p>* If multifunction roll unit is used.</p>
<b>Media Width</b>	<p>Roll Feed: 6" - 60" (152.4 mm - 1,524 mm)</p> <p>Cut Sheet: 6" - 60" (152.4 mm - 1,524 mm)</p>
<b>Media Cutter</b>	Automatic horizontal cutting (Rotary cutter): standard
<b>Media Thickness</b>	0.002" - 0.03" (0.07 mm - 0.8 mm)
<b>Media Core Sizes</b>	2" Core Standard, 2"/3" Core Roll Holder Set PRO-2600 (RH2-29), PRO-4600 (RH2-46), PRO-6600 (RH2-66)
<b>Maximum Roll Outer Diameter</b>	6.7" or less (170 mm or less)

<b>Media Output</b>	Catch Basket
<b>Printing Software Utilities</b>	Accounting Manager, Device Management Console, Direct Print Plus, Free Layout Plus, imagePROGRAF Printer Driver for Windows®/Mac®, Media Configuration Tool, PosterArtist, Canon Print Service, Professional Print & Layout
<b>Operating System</b>	Windows 7 (32/64-bit), Windows 8.1 (32/64-bit), Windows 10 (32/64-bit), Windows 11 (64-bit), Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022 (64-bit) Macintosh OS v10.12.6 - v13x
<b>Print Language</b>	SGRaster (Swift Graphic Raster), PDF, JPEG
<b>Interface</b>	Standard (Built-in): USB 2.0 Hi-Speed, 10/100/1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g/n)* *Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.
<b>Power Supply</b>	AC 100 – 240V (50 – 60 Hz)
<b>Power Consumption</b>	Max: Approx 85W Standby: Approx. 1.7W Power Off: Approx 0.1W
<b>Certifications</b>	ENERGY STAR® (Worldwide), EPEAT Gold
<b>Operational Environment</b>	Temperature: 59 – 86 °F (15 – 30 °C) Relative Humidity: 10 – 80% (Non Condensation)
<b>Printer Dimensions (W x D x H) and Weight</b>	With stand and basket open: 78.7" x 38.7" x 46", 377 lbs Main unit with pallet: 87.7" x 36.0" x 40.4", 490 lbs
<b>Options</b>	<ul style="list-style-type: none"> <li>• Multifunction Roll Unit - PRO-2600 (RU-23) &amp; PRO-4600 (RU-43)</li> <li>• 2/3" Roll Holder Set PRO-2600</li> </ul>
<b>User-replaceable items</b>	<ul style="list-style-type: none"> <li>• Ink Tank: PFI-3100 (160 ml)/PFI-2100 MBK (160 ml), PFI-3300 (330 ml)/ PFI-2300 MBK (330 ml), PFI-3700 (700 ml)/PFI-2700 MBK (700 ml)</li> <li>• Print Head (PF-10)</li> <li>• Maintenance Cartridge (MC-30)</li> <li>• Cutter Blade (CT-07)</li> </ul>